

Streamline

Model HTLP (5,000 lb to 6,000 lb Drawbar pull)



Standard Features

- F-N-R shifter
- Keyless anti-restart ignition switch
- Two Headlights
- Modular lighting includes: Tail/Stop Lights, Back-up Light & Turn Signals
- Volt Meter
- Water Temperature Gauge
- Engine Oil Pressure Gauge
- Engine Hour Meter Gauge
- Fuel Level Gauge
- Standard driver and passenger seat
- Driver hitch release

Specifications subject to improvement and/or change without notice

Specifications for Model: STREAMLINE (5k-6k) Towing Tractor

Drawbar Pull Available

<u>Model</u>	<u>DBP</u>	<u>(+/-) GVW</u>	<u>(+/-) Towed Wt</u>
HLP505,000 lbs6,500 lbs 50,000 lbs
HLP606,000 lbs7,200 lbs 60,000 lbs

Towed weight on a dry surface up to a 3% grade

Dimensions

Length114" (2896 mm)
Width55" (1397 mm)
Height61" (1549 mm)
Height w/cab81" (2070 mm)
Wheel Base 70" (1778 mm)
Ground Clearance 6" (152 mm)

Available Diesel Engines (naturally aspirated) Equipped with Gauge & Sender system

- *Cummins*
- *Perkins*

Available Diesel Turbo Engine

- *Cummins*

Drive Axle

- Heavy duty Harlan – 10,000lb Capacity

Steer Axle

- Heavy duty Harlan with 1 1/8" King Pin

Suspension

- Shocks & Leaf Springs on front and rear axles

Brakes

Service:

- Dual Split System
- Hydraulic/Hydraulic
- Dual rear disc w/optional front disc brakes
- Other brake options available upon request

Parking:

- Mechanical Drum (lever activated)

Towing Coupler

- E-Hitch – 1"
- Other couplers available on request

Transmission

- Ford C-6 Automatic
- 3-speeds forward, 1 reverse

Electrical

- 12 V, Negative ground

Cooling System

- Dual core cross-flow radiator with 3.75 quart capacity
- Oil cooled radiator with the Deutz engine

Steering System

- Hydraulic steering (Saginaw power assisted)

Turning Radius

- 135" (3429mm)

Tires

- Front: 6.50 x 10
- Rear: LT215/80R x16